

LUTZE TOP-T Locknuts Metal

Metal Locknuts for use with NPT, PG, Metric and EMC Fittings



Characteristics

- Hexagonal locknut for secure tightening of cable fittings and accessories

Specifications

Temperature range up to +200°C/+392°F
Material Brass, nickel plated

Part No.	For Thread Type	OD - Ø mm	SW mm	H mm	PU
NPT					
LMNPT38	NPT 3/8"	26.5	24	5	5
LMNPT12	NPT 1/2"	26.5	24	5	5
LMNPT34	NPT 3/4"	37.5	34	6	5
LMNPT10	NPT 1"	46.4	42	6	5
LMNPT1014	NPT 1 1/4"	57.4	52	7	1
LMNPT1012	NPT 1 1/2"	65.1	60	7	1
LMNPT20	NPT 2"	81.8	74	8	1
LMNPT2012	NPT 2 1/2"	89	80	10	1
LMNPT30	NPT 3"	105.5	95	10	1
PG					
LMPG7	PG 7	16.6	15	2.8	20
LMPG9	PG 9	20	18	2.8	20
LMPG11	PG 11	23.5	21	3	20
LMPG13	PG 13.5	25.5	23	3	20
LMPG16	PG 16	29	26	3	20
LMPG21	PG 21	35.5	32	3.5	20
LMPG29	PG 29	45	41	4	10
LMPG36	PG 36	56	51	5	10
LMPG42	PG 42	66	60	5	5
LMPG48	PG 48	70.5	64	5.5	5
METRIC					
LMM12	M12x1.5	16.6	15	2.8	20
LMM16	M16x1.5	21	19	3	20
LMM20	M20x1.5	26.5	24	3.5	20
LMM25	M25x1.5	33	30	4	20
LMM32	M32x1.5	39.5	36	5	10
LMM40	M40x1.5	51	46	5	5
LMM50	M50x1.5	66	60	5	1
LMM63	M63x1.5	77	70	6	1
LMM75	M75x1.5	89	80	7	1
LMM90	M90x1.5	112	100	8	1
EMC - METRIC CUTTING TEETH					
LMM12-C	M12x1.5	16.5	15	3.3	10
LMM16-C	M16x1.5	21	19	3.5	10
LMM20-C	M20x1.5	26.5	24	3.5	10
LMM25-C	M25x1.5	33	30	3.5	10
LMM32-C	M32x1.5	39.5	36	4	5
LMM40-C	M40x1.5	51	46	4.6	5
LMM50-C	M50x1.5	66	60	5.6	1

EMC Metric Locknuts with Cutting Teeth

- For secure tightening of EMC cable fittings
- To cut through paint layers or powder coatings ensuring optimal contact
- Increased vibration resistance

Specifications are subject to change without prior notice